Data sheet


HP Coated Paper, 3-in Core

This product is compatible with HP Latex, Dye and Pigmented inks.



The HP large format printing system—the complete solution

HP Designjet, HP Latex, and HP Scitex Printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



Create presentation-quality images

Accomplish more with consistent results

From line drawings to illustrations and light ink-density graphics, see high-quality, consistent image quality print to print and roll to roll.

Improve your response time

Handle prints with confidence right off the printer. An enhanced coating provides ink abrasion resistance to help you deliver on quick turnaround times.

Do more, with the environment in mind

Gain versatility with this premium bright white paper. From working comps and design proofs to fine line drawings and illustrations, meet the project needs and the environmental objectives of your company and clients with a recyclable paper.

Target customers	Applications	Benefits
Architects	Posters and presentations	Crisp text and graphics, consistent high-quality results
Engineers	POP and retail displays	Resistance to ink abrasion for easy handling
Geographic Information Systems (GIS) professionals	Geographic Information Systems (GIS)	Recyclable through commonly available programs
Graphic designers	Architecture (AEC) and engineering (MCAD)	
Print service providers		

Technical specifications



HP Coated Paper, 3-in Core
For the latest ICC profiles/paper presets, please visit globalBMG.com/hp/paperpresets.

Weight	90 g/m² per ISO 536 Test Method, (24 lbs)			
Thickness	114 microns/4.5 mil per ISO 534 Test Method			
Opacity	93% per TAPPI T-425 Test Method			
Brightness	89% per TAPPI T-452 Test Method			
Whiteness	145 per CIE Whiteness ISO 11475 D65/10° Outdoor Daylight Test Method			
Finish	Matte			
Operating temperature	15 to 35° C / 59 to 95° F			
Operating humidity	20 to 80% RH			
Dry time	Immediate (at 23° C, 50% RH)			
Lamination	Yes, with commercially available thermal and pressure-sensitive laminate films			
Shelf life	2 years, unopened in original packaging			
Storage temperature	0 to 40° C / 32 to 104° F			
Storage humidity	5 to 95% RH			
Recyclability	Recyclable through commonly available recycling programs			
Country of origin	Product of Germany			
Ordering information	**Product numbers**	**Roll sizes**	**UPC codes**	**Region**
	D9R21A	914 mm x 61 m (36 in x 200 ft)	848412009873	North America, Europe, Asia
	D9R22A	1067 mm x 61 m (42 in x 200 ft)	848412009880	North America, Europe, Asia
	D9R23A	1372 mm x 61 m (54 in x 200 ft)	848412009897	North America, Europe, Asia
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/mediawarranties			

For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2015 Hewlett-Packard Development Company. © 2014 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of Hewlett-Packard Company and is used by Brand Management Group on license from Hewlett-Packard Company.

January 2015