




HP Permanent Gloss Adhesive Vinyl



The HP large format printing system—the complete solution

HP Latex printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



Choose this REACH compliant,¹ economical vinyl

Grab attention with bright, vibrant image quality

Capture vibrant graphic detail, display brilliant color. From event signage to retail displays, achieve a high-quality look with this versatile, easy-to-handle, quick-mount self-adhesive vinyl—ideal for a wide range of indoor and outdoor applications.

Count on lasting, durable results

Depend on lasting results. Prints achieve 3 years unlaminated display permanence outdoors;² 3 years in-window. You get optimal results—including weather-resistance without additional lamination—using HP Latex Inks.

Differentiate with environmental certification

Offer a vinyl that complies with high health standards. HP Permanent Gloss Adhesive Vinyl is REACH compliant—a regulation of the European Union adopted to improve the protection of human health and the environment.

¹ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](https://www.hp.com/go/reach).

² Outdoor display permanence rating according to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. For more information, see [HPLFMedia.com/hp/printpermanence](https://www.hp.com/go/printpermanence).

| Target customers | Applications | Benefits |
|-------------------------|-------------------------------|--|
| Print service providers | Trade show and event displays | Vibrant graphic detail |
| | Signage | Brilliant color |
| | POP and retail displays | Gloss finish |
| | | Highly opaque for a high-quality look |
| | | Easy to handle and mount |
| | | Outdoor display permanence 3 years unlaminated, up to 3 years laminated |
| | | Indoor, in-window display permanence 3 years unlaminated, up to 10 years laminated |
| | | Permanent adhesive |
| | | Provides reassurance with REACH compliance |

Technical specifications



HP Permanent Gloss Adhesive Vinyl

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit [HPLFMedia.com/paperpresets](https://hplfmedia.com/paperpresets).

| | | | | |
|--|--|-----------------------------------|------------------|---------------|
| Ink technology | Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks | | | |
| Weight (Without liner) | 145 g/m ² per ISO 536 Test Method | | | |
| Weight (With liner) | 270 g/m ² per ISO 536 Test Method | | | |
| Thickness (Without liner) | 121 microns/4.8 mil per ISO 20534 Test Method | | | |
| Thickness (With liner) | 248 microns/9.8 mil per ISO 20534 Test Method | | | |
| Opacity | Greater than 95% per TAPPI T-425 Test Method | | | |
| Tensile strength | MD > 40 N/25 mm / CD > 40 N/25 mm per ASTM D 882-02 | | | |
| Brightness | 83% per TAPPI T-452 Test Method | | | |
| Whiteness | 78 per CIE Whiteness (D65/10°) | | | |
| Finish | Gloss | | | |
| Operating temperature | 15 to 35° C / 59 to 95° F | | | |
| Operating humidity | 30 to 80% RH | | | |
| Display permanence (Commercial in-window) | 3 years (under review) unlaminated with Original HP 831, HP 871, or HP 881 Latex Inks ³ | | | |
| Display permanence (Outdoor) | 3 years unlaminated with Original HP 831, HP 871, or HP 881 Latex Inks | | | |
| Water resistance | Water-resistant with Original HP 831, HP 871, or HP 881 Latex ⁴ | | | |
| Dry time | Instant dry | | | |
| Lamination | Yes, cold | | | |
| Shelf life | 1 year, unopened in original packaging | | | |
| Storage temperature | 5 to 40° C / 41 to 104° F | | | |
| Storage humidity | 5 to 95% RH | | | |
| Country of origin | Product of China | | | |
| Ordering information | Product numbers | Roll sizes | UPC codes | Region |
| | J3H62A | 914 mm x 45,7 m (36 in x 150 ft) | 848412014907 | Worldwide |
| | J3H63A | 1067 mm x 45,7 m (42 in x 150 ft) | 848412009293 | Worldwide |
| | J3H64A | 1372 mm x 45,7 m (54 in x 150 ft) | 848412009309 | Worldwide |
| | J3H65A | 1372 mm X 91,4 m (54 in X 300 ft) | 848412014938 | Worldwide |
| | J3H66A | 1524 mm x 45,7 m (60 in x 150 ft) | 848412009316 | Worldwide |
| | J3H67A | 1524 mm x 91,4 m (60 in x 300 ft) | 848412009323 | Worldwide |
| Warranty | HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see HPLFMedia.com/go/mediawarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus . | | | |

³ Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day. For more information, see [HPLFMedia.com/hp/printpermanence](https://hplfmedia.com/hp/printpermanence).

⁴ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: [HPLFMedia.com/hp/printpermanence](https://hplfmedia.com/hp/printpermanence).

REACH

For detailed information on the HP large format printing materials portfolio and to order, visit [HPLFMedia.com](https://hplfmedia.com)

© 2020 HP Development Company, L.P. © 2020 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group on license from HP Development Company, L.P.

