




# HP 13-oz Prime Gloss Banner



## The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



<sup>1</sup> Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see [HPLFMedia.com/hp/printpermanence](http://HPLFMedia.com/hp/printpermanence).

<sup>2</sup> NFPA 701 approved fire certification.

## Produce durable, brilliant banners

### Take on demanding display conditions

From long-lasting indoor displays to demanding outdoor display conditions, this durable front-lit banner material can handle it all. Brilliant image quality is preserved in water<sup>1</sup>- and tear-resistant prints. The polyester scrim reinforcement provides excellent rip-stop qualities and extra strength when grommeting.

### Offer brilliant, vivid images that drape well

Achieve a professional finish with a material that's easy to handle and hang, grommet, or stitch. HP 13-oz Prime Gloss Banner is REACH compliant<sup>4</sup>—a regulation of the European Union adopted to improve the protection of human health and the environment.

### Gain efficiency while providing outstanding color fidelity

Save time and gain efficiency with ICC profiles that help you get the color you need quickly. Applications include indoor or outdoor signs and graphics, banner stands, POP displays, and hanging banners. Designed for use with HP Latex Inks, as well as solvent, low-solvent, and UV-curable inks.

Target customers	Applications	Benefits
Sign shops	Trade show and event banners	Economical
Print service providers	Point-of-sale, retail displays	Gloss finish
Quick printers	Indoor and short-term outdoor banners	Water-resistant prints for a wide range of applications <sup>1</sup>
Hotels, restaurants, and entertainment venues	Event and promotional signage	Bright white point for striking image contrast
	Pop-up banner stand graphics	NFPA 701 flame resistance <sup>2</sup>
		Provides environmental reassurance with REACH compliance <sup>4</sup>

## Technical specifications



### HP 13-oz Prime Gloss Banner

For the latest ICC profiles/paper presets, please visit [HPLFMedia.com/hp/paperpresets](https://HPLFMedia.com/hp/paperpresets).

<b>Ink technology</b>	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks			
<b>Weight</b>	440 g/m <sup>2</sup> (13 oz/yd <sup>2</sup> ) per ISO 536 Test Method			
<b>Thickness</b>	355 microns / 14 mil per ISO 534 Test Method			
<b>Yarn dtex</b>	1000 x 1000 dtex per DIN EN ISO 2060			
<b>Tensile strength</b>	1369/1044 N/5 cm (154/117.4 lb/inch) per DIN EN ISO 1421			
<b>Tear strength</b>	245.4/152.4 N (57.2/34.3 lb) per DIN 53363			
<b>Opacity</b>	98% per TAPPI T-425 Test Method			
<b>Brightness</b>	Greater than 87% per TAPPI T-452 Test Method			
<b>Whiteness</b>	96 per CIE Ganz 82 Test Method			
<b>Finish</b>	Gloss			
<b>Operating temperature</b>	13 to 43° C (55 to 109° F)			
<b>Operating humidity</b>	10 to 70% RH			
<b>Water resistance</b>	Water resistant with Original HP Latex Inks <sup>3</sup>			
<b>Dry time</b>	Immediate			
<b>Flame resistance</b>	NFPA 701 approved fire certification			
<b>Shelf life</b>	12 months at recommended temperature and humidity			
<b>Environmental</b>	REACH compliant <sup>4</sup>			
<b>Storage temperature</b>	4 to 32° C (39 to 89° F)			
<b>Storage humidity</b>	10 to 70% RH			
<b>Country of origin</b>	Product of Vietnam			
<b>Ordering information</b>	<b>Product numbers</b>	<b>Roll sizes</b>	<b>UPC codes</b>	<b>Region</b>
	1A718A	965 mm x 50 m (38 in x 164 ft)	848412025798	United States, Canada, and Latin America
	1A719A	1372 mm x 50 m (54 in x 164 ft)	848412025804	United States, Canada, and Latin America
	1A720A	1600 mm x 50 m (63 in x 164 ft)	848412025811	United States, Canada, and Latin America
<b>Warranty</b>	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see <a href="https://HPLFMedia.com/hp/MediaWarranties">HPLFMedia.com/hp/MediaWarranties</a> . To obtain warranty service, please contact Brand Management Group customer support at <a href="https://HPLFMedia.com/hp/en/contactus">HPLFMedia.com/hp/en/contactus</a> .			

<sup>3</sup> Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see [HPLFMedia.com/hp/printpermanence](https://HPLFMedia.com/hp/printpermanence).

<sup>4</sup> As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at [HP Printing Products and Consumable Supplies](https://HP Printing Products and Consumable Supplies). Logo source: Copyright European Chemicals Agency.



For detailed information on the HP large format printing materials portfolio and to order, visit [HPLFMedia.com](https://HPLFMedia.com)

