




HP Coated Paper, 3-in Core

This product is compatible with HP Latex, Dye and Pigmented inks.



The HP large format printing system—the complete solution

HP Designjet, HP Latex, and HP Scitex Printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



Create presentation-quality images

Accomplish more with consistent results

From line drawings to illustrations and light ink-density graphics, see high-quality, consistent image quality print to print and roll to roll.

Improve your response time

Handle prints with confidence right off the printer. An enhanced coating provides ink abrasion resistance to help you deliver on quick turnaround times.

Do more, with the environment in mind

Gain versatility with this premium bright white paper. From working comps and design proofs to fine line drawings and illustrations, meet the project needs and the environmental objectives of your company and clients with a recyclable paper.

| Target customers | Applications | Benefits |
|--|---|--|
| Architects | Posters and presentations | Crisp text and graphics, consistent high-quality results |
| Engineers | POP and retail displays | Resistance to ink abrasion for easy handling |
| Geographic Information Systems (GIS) professionals | Geographic Information Systems (GIS) | Recyclable through commonly available programs |
| Graphic designers | Architecture (AEC) and engineering (MCAD) | |
| Print service providers | | |

Technical specifications



HP Coated Paper, 3-in Core

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

| | | | | |
|------------------------------|--|---------------------------------|------------------|-----------------------------|
| Weight | 90 g/m ² per ISO 536 Test Method, (24 lbs) | | | |
| Thickness | 114 microns/4.5 mil per ISO 534 Test Method | | | |
| Opacity | 93% per TAPPI T-425 Test Method | | | |
| Brightness | 89% per TAPPI T-452 Test Method | | | |
| Whiteness | 145 per CIE Whiteness ISO 11475 D65/10° Outdoor Daylight Test Method | | | |
| Finish | Matte | | | |
| Operating temperature | 15 to 35° C / 59 to 95° F | | | |
| Operating humidity | 20 to 80% RH | | | |
| Dry time | Immediate (at 23° C, 50% RH) | | | |
| Lamination | Yes, with commercially available thermal and pressure-sensitive laminate films | | | |
| Shelf life | 2 years, unopened in original packaging | | | |
| Storage temperature | 0 to 40° C / 32 to 104° F | | | |
| Storage humidity | 5 to 95% RH | | | |
| Recyclability | Recyclable through commonly available recycling programs | | | |
| Country of origin | Product of Germany | | | |
| Ordering information | Product numbers | Roll sizes | UPC codes | Region |
| | D9R21A | 914 mm x 61 m (36 in x 200 ft) | 848412009873 | North America, Europe, Asia |
| | D9R22A | 1067 mm x 61 m (42 in x 200 ft) | 848412009880 | North America, Europe, Asia |
| | D9R23A | 1372 mm x 61 m (54 in x 200 ft) | 848412009897 | North America, Europe, Asia |
| Warranty | HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/mediawarranties | | | |



For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2015 Hewlett-Packard Development Company. © 2014 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of Hewlett-Packard Company and is used by Brand Management Group on license from Hewlett-Packard Company.

January 2015

