
# HP Everyday Adhesive Matte Polypropylene, 3-in Core





## The HP large format printing system—the complete solution

HP Designjet, HP Latex, and HP Scitex Printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



## High-quality prints for your day-to-day production

#### Produce eye-catching displays

See outstanding image quality. Work with the wide color gamut and smooth transitions delivered by this matte polypropylene material and produce quality prints from line drawings to photo-quality POP displays.

#### **Gain efficiency**

Help keep your production process moving smoothly. This easy-to-use film features a permanent self adhesive for secure, reliable mounting.

#### Make the versatility of this material work for you

ICC profiles help you get the right color, right away. Take advantage of compatibility with Original HP Latex, dye, and pigmented inks on this versatile, easy-to-use printing material.

Target customers	Applications	Benefits
Print service providers	POP and retail displays	Outstanding image quality for day-to-day production
Retail store in-house printing	Trade show and event displays	A permanent self-adhesive for secure, reliable mounting
Event designers	Temporary exhibitions	
Advertising agencies	Architecture competitions	5
Geographic Information Systems (GIS)		
Government (printing self adhesive maps)	F-	

### **Technical specifications**



#### HP Everyday Adhesive Matte Polypropylene, 3-in Core

For the latest ICC profiles/paper presets, please visit globalBMG.com/hp/paperpresets.

120 g/m² per ISO 536 Test Method				
168 g/m² per ISO 536 Test Method				
180 microns/7.1 mil per ISO 534 Test Method				
215 microns/8.5 mil per ISO 534 Test Method				
Greater than 96% per TAPPI T-425 and ISO 2471 Test Methods				
101% per ISO 2470 Test Method				
Greater than 120 per ISO 11476 Test Method				
150 per ISO 11475 Test Method				
Matte				
15 to 35° C / 59 to 95° F				
20 to 80% RH				
Less than 2 minutes (at 23° C, 50% RH)				
Yes				
2 years, unopened in original packaging				
15 to 35° C / 59 to 95° F				
15 to 30% RH				
Product of China				
Product numbers	Roll sizes	UPC codes	Region	
D9R24A	914 mm x 30,5 m (36 in x 100 ft)	848412009798	North America, Europe, Asia	
D9R25A	1067 mm x 30,5 m (42 in x 100 ft)	848412009804	North America, Europe, Asia	
D9R26A	1270 mm x 30,5 m (50 in x 100 ft)	848412009811	North America, Europe, Asia	
D9R27A	1524 mm x 30,5 m (60 in x 100 ft)	848412009828	North America, Europe, Asia	
HP offers a range of self-adhesive materials with warranties that guarantee these products to be free of materia				
or coating flaws and defects that affect the final use of the print and meet HP published specifications. For warranty statement please see globalBMG.com/hp/mediawarranties.				
	168 g/m² per ISO 180 microns/7.1 r 215 microns/8.5 Greater than 96% 101% per ISO 247 Greater than 12O 150 per ISO 1147 Matte 15 to 35° C / 59 to 20 to 80% RH Less than 2 minu Yes 2 years, unopene 15 to 35° C / 59 to 15 to 30% RH Product of China Product numbers D9R24A D9R25A D9R26A D9R27A HP offers a range or coating flaws a	168 g/m² per ISO 536 Test Method 180 microns/7.1 mil per ISO 534 Test Method 215 microns/8.5 mil per ISO 534 Test Method Greater than 96% per TAPPI T-425 and ISO 2471 Test M 101% per ISO 2470 Test Method Greater than 120 per ISO 11476 Test Method 150 per ISO 11475 Test Method Matte 15 to 35° C / 59 to 95° F 20 to 80% RH Less than 2 minutes (at 23° C, 50% RH) Yes 2 years, unopened in original packaging 15 to 35° C / 59 to 95° F 15 to 30% RH Product of China  Product numbers Roll sizes  D9R24A 914 mm x 30,5 m (36 in x 100 ft) D9R25A 1067 mm x 30,5 m (50 in x 100 ft) D9R27A 1524 mm x 30,5 m (50 in x 100 ft) HP offers a range of self-adhesive materials with warran or coating flaws and defects that affect the final use of t	168 g/m² per ISO 536 Test Method  180 microns/7.1 mil per ISO 534 Test Method  215 microns/8.5 mil per ISO 534 Test Method  Greater than 96% per TAPPI T-425 and ISO 2471 Test Methods  101% per ISO 2470 Test Method  Greater than 120 per ISO 11476 Test Method  150 per ISO 11475 Test Method  Matte  15 to 35° C / 59 to 95° F  20 to 80% RH  Less than 2 minutes (at 23° C, 50% RH)  Yes  2 years, unopened in original packaging  15 to 35° C / 59 to 95° F  15 to 30% RH  Product of China  Product numbers Roll sizes UPC codes  D9R24A 914 mm x 30,5 m (36 in x 100 ft) 848412009798  D9R25A 1067 mm x 30,5 m (42 in x 100 ft) 848412009804  D9R26A 1270 mm x 30,5 m (50 in x 100 ft) 848412009811  D9R27A 1524 mm x 30,5 m (60 in x 100 ft) 848412009828  HP offers a range of self-adhesive materials with warranties that guarantee thor coating flaws and defects that affect the final use of the print and meet HP	

For detailed information on the HP large format printing materials portfolio and to order, visit globalBMG.com/hp.

Sign up for updates globalBMG.com/hp/getupdated





© 2014 Hewlett-Packard Development Company. © 2014 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of Hewlett-Packard Company and is used by Brand Management Group on license from Hewlett-Packard Company.