
# **HP Permanent Gloss Adhesive Vinyl**





#### The HP large format printing system—the complete solution

HP Latex printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



printing materials

- This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.
- Outdoor display permanence rating according 2 to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. For more information, see HPLFMedia.com/hp/printpermanence.

# Choose this REACH compliant,<sup>1</sup> economical vinyl

## Grab attention with bright, vibrant image quality

Capture vibrant graphic detail, display brilliant color. From event signage to retail displays, achieve a high-quality look with this versatile, easy-to-handle, quick-mount self-adhesive vinyl—ideal for a wide range of indoor and outdoor applications.

## Count on lasting, durable results

Depend on lasting results. Prints achieve 3 years unlaminated display permanence outdoors;<sup>2</sup> 3 years in-window. You get optimal results—including weather-resistance without additional lamination—using HP Latex Inks.

#### Differentiate with environmental certification

Offer a vinyl that complies with high health standards. HP Permanent Gloss Adhesive Vinyl is REACH compliant—a regulation of the European Union adopted to improve the protection of human health and the environment.

Target customers	Applications	Benefits
Print service providers	Trade show and event displays	Vibrant graphic detail
	Signage	Brilliant color
	POP and retail displays	Gloss finish
		Highly opaque for a high-quality look
		Easy to handle and mount
		Outdoor display permanence 3 years unlaminated, up to 3 years laminated
		Indoor, in-window display permanence 3 years unlaminated, up to 10 years laminated
		Permanent adhesive
		Provides reassurance with REACH compliance

## **Technical specifications**



#### **HP Permanent Gloss Adhesive Vinyl**

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit HPLFMedia.com/paperpresets.

Weight (Without liner)	150 g/m² per ISO 536 Test Method					
Weight (With liner)	270 g/m² per ISO 536 Test Method					
Thickness (Without liner)	121 microns/4.8 mil per ISO 20534 Test Method					
Thickness (With liner)	248 microns/9.8 mil per ISO 20534 Test Method					
Opacity	Greater than 95% per TAPPI T-425 Test Method					
Tensile strength	MD > 40 N/25 mm / CD > 40 N/25 mm per ASTM D 882-02					
Brightness	83% per TAPPI T-452 Test Method					
Whiteness	78 per CIE Whiteness (D65/10°)					
Finish	Gloss					
Operating temperature	15 to 35° C / 59 to 95° F					
Operating humidity	30 to 80% RH					
Display permanence (Commercial in-window)	3 years (under review) unlaminated with Original HP 831, HP 871, or HP 881 Latex $Inks^3$					
Display permanence (Outdoor)	3 years unlaminated with Original HP 831, HP 871, or HP 881 Latex Inks					
Water resistance	Water-resistant with Original HP 831, HP 871, or HP 881 Latex <sup>4</sup>					
Dry time	Instant dry					
Lamination	Yes, cold					
Shelf life	1 year, unopened in original packaging					
Storage temperature	5 to 40° C / 41 to 104° F					
Storage humidity	5 to 95% RH					
Country of origin	Product of China					
Ordering information	<b>Product numbers</b>	Roll sizes	UPC codes	Region		
	J3H62A	914 mm x 45,7 m (36 in x 150 ft)	848412014907	Worldwide		
	J3H63A	1067 mm x 45,7 m (42 in x 150 ft)	848412009293	Worldwide		
	J3H64A	1372 mm x 45,7 m (54 in x 150 ft)	848412009309	Worldwide		
	J3H65A	1372 mm X 91,4 m (54 in X 300 ft)	848412014938	Worldwide		
	J3H66A	1524 mm x 45,7 m (60 in x 150 ft)	848412009316	Worldwide		
	J3H67A	1524 mm x 91,4 m (60 in x 300 ft)	848412009323	Worldwide		
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see HPLFMedia.com/go/mediawarranties. To obtain warranty service, please conta Brand Management Group customer support at <u>HPLFMedia.com/hp/en/contactus</u>					

<sup>3</sup> Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant calculation assumes 6,000 Lux/12 hr day. For more information, see <u>HPLFMedia.com/hp/printpermanence</u>.

<sup>4</sup> Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: <u>HPLFMedia.com/hp/printpermanence</u>.



#### For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2019 HP Development Company, L.P. © 2019 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group on license from HP Development Company, L.P.

