HP Gloss Polymeric Overlaminate



High-performance polymeric gloss overlaminate and print film



The HP large format printing system—the complete solution

HP Latex printers, Original HP Latex Inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



- With HP 871 and 831 Latex Inks, over 10 years laminated display permanence for indoor home or office, commercial in-window, and outdoor displays.
- As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies. Logo source: Copyright European Chemicals Agency.
- Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.
- ⁴ B1 approved fire certification.

Produce brilliant image quality—print film doubles as overlaminate

Gain double value with prints and overlaminate

Print high-quality, detailed graphics with this high-performance, calendered polymeric vinyl with a high-gloss finish for indoor and outdoor signs and vehicle graphics. HP Gloss Polymeric Overlaminate can also double as an overlaminate for printed images with the utmost protection. Provides durable print performance with over 10 years laminated display permanence.¹

Differentiate with environmental certifications

Offer a vinyl that complies with high health standards. HP Gloss Polymeric Overlaminate is flame-resistant⁴ and REACH compliant²—a regulation of the European Union adopted to improve the protection of human health and the environment.

Save time with a reliable, total HP solution

Original HP printing materials, Original HP inks, and HP large format printers are designed to work together as a system to provide reliable, consistent, quality results that help save time. Prints produced with HP Latex Inks also provide a better approach with end-to-end environmental sustainability.³

Applications	Benefits		
Overlaminate solution	High-performance polymeric calendered vinyl with dual use: brilliant image quality and an overlaminate for protection		
Print film solution	Ease of handling with the lay-flat double- sided, PE-coated silicone release liner		
Indoor and outdoor signage	Provides reassurance with REACH compliance ¹		
Window graphics Compatible with Original HP solvent, low-solvent, and U'			
Fleet graphics	Class B1 flame-resistant ⁴		
	Overlaminate solution Print film solution Indoor and outdoor signage Window graphics		



Technical specifications

HP Gloss Polymeric Overlaminate

For the latest ICC profiles/paper presets, please visit <u>HPLFMedia.com/hp/paperpresets</u>.

Ink technology	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks					
Thickness (base vinyl)	76 microns/3 mil per ISO 20534 Test Method					
Base vinyl	Calendered high-performance polymeric vinyl					
Liner	140 g/m², double-sided PE-coated silicone paper					
Adhesive	Clear, permanent pressure-sensitive adhesive					
Finish	Gloss, greater than 70 gloss units at 60° reflection					
Display permanence (Outdoor unprinted)	In testing					
Display permanence (Outdoor)	In testing					
Display permanence (Indoor home or office)	In testing					
Display permanence (Commercial in-window)	Over 5 years unlaminated, over 10 years laminated with HP 871 and 831 Latex Inks⁵					
Water resistance	Water resistant with HP 871 and 831 Latex Inks ⁶					
Minimum application temperature	4 to 35°C (39 to 95°F) on clean, dry surfaces					
Service temperature	-28 to 65°C (-18 to 149°F)					
Operating temperature	15 to 35°C (59 to 95°F)					
Operating humidity	40 to 60% RH					
Lamination	Cold lamination; recommend using HP Matte or Gloss Polymeric Overlaminates					
Shelf life	2 years, unopened in original packaging					
Storage temperature	21 to 24°C (69 to 75°F)					
Storage humidity	50% RH					
Flame resistance	B1 approved fire certifications					
Environmental	REACH ⁷ and RoHS compliant					
Country of origin	Product of the U	Product of the United States				
Ordering information	Product numbers	Roll sizes	UPC codes	Region		
	6GA31A	1067 mm x 50 m (42 in x 164 ft)	848412024838	Europe, Middle East, and Africa		
	6GA32A	1372 mm x 50 m (54 in x 164 ft)	848412024845	Europe, Middle East, and Africa		
	6GA34A	1524 mm x 50 m (60 in x 164 ft)	848412024852	Europe, Middle East, and Africa		
Warranty	statement, pleas	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/go/mediawarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .				

⁵ Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6.000 Lux/12 hr day. For more information, see HPLFMedia.com/hp/printpermanence.

⁷ As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies. Logo source: Copyright European Chemicals Agency.



For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2019 HP Development Company, L.P. © 2019 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.



⁶ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: <u>HPLFMedia.com/hp/printpermanence</u>.