




HP Professional Satin Photo Paper



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Experience outstanding, heavyweight, resin-coated photo paper for photographic printing

Enjoy high-performance photo printing

Now you can print high-end photography, posters, and retail graphics for either custom or high-volume projects with your HP Latex printer on this versatile resin-coated photo paper.

Move quickly and efficiently through production

There's no need to wait; print and deliver to provide quick turnarounds for your customers. This heavyweight photo paper (275 g/m²) also provides increased stability for handling high-volume production. Meet the environmental objectives of your company—and your clients—with this FSC®-certified paper.¹

Achieve spot-on, dynamic color

The bright-white finish provides a high dynamic range and a wide color gamut for color-critical, eye-catching reproductions on a satin finish.

Target customers	Applications	Benefits
Point-of-purchase providers	Photo enlargements	Prints come out completely dry, enabling production printing
Trade show and exhibit companies	Art and décor reproductions	Heavy, thick construction for easy handling
Photo and art reproduction houses	Point-of-purchase displays	Wide color gamut and bright-white surface
	Trade show and event displays	FSC®-certified paper ¹

Technical specifications



HP Professional Satin Photo Paper

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/paperpresets.

Ink compatability	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks
Weight	275 g/m ² per ISO 536 Test Method
Thickness	248 microns/9.8 mil per ISO 534 Test Method
Opacity	>96% per TAPPI T-425 Test Method
Brightness	96 per TAPPI T-452 Test Method
Whiteness	130 per ISO 11475 Test Method
Finish	Satin
Operating temperature	15 to 35° C / 59 to 95° F
Operating humidity	30 to 80% RH
Dry time	Instant dry
Lamination	Yes, cold
Shelf life	1 year, unopened in original packaging
Storage temperature	0 to 40° C / 32 to 104° F
Storage humidity	5 to 95% RH
Environmental	FSC®-certified paper ¹
Country of origin	Product of Germany

Ordering information	Product numbers	Roll sizes	UPC codes	Region
	E4J46A	914 mm x 30,5 m (36 in x 100 ft)	848412014501	Worldwide
	E4J47A	1067 mm x 30,5 m (42 in x 100 ft)	848412014518	Worldwide
	E4J48A	1372 mm x 30,5 m (54 in x 100 ft)	848412014525	Worldwide
	E4J49A	1524 mm x 30,5 m (60 in x 100 ft)	848412014532	Worldwide

Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see HPLFMedia.com/mediawarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .
-----------------	--

¹ HP has a policy for offering Forest Stewardship Council® (FSC®)-certified papers that are sourced from FSC®-certified forests and other controlled sources. BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions.



The mark of responsible forestry

For detailed information on the HP large format print media portfolio and to order, visit HPLFMedia.com

© 2023 HP Development Company, L.P. © 2023 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group on license from HP Development Company, L.P.

