




HP Recycled¹ Removable Adhesive Fabric, 3-in Core



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Print high-quality, repositionable graphics that stick to non-porous surfaces

Easy-to-install, reposition, and remove

Enjoy the ease of working with this repositionable adhesive-back fabric that is easy to install, reposition, and remove with virtually no residue. The special adhesive is designed to stick to non-porous surfaces to create seamless, photographic image quality wall and floor graphics.

Made with recycled water bottles² and coating materials

HP Recycled¹ Removable Adhesive Fabric is made with recycled water bottles² and coating materials. Recycling beverage containers (and other materials) saves energy, reduces greenhouse gas emissions, and diverts material from landfills.³

Grab attention with vibrant image quality for a variety of applications

Capture realistic graphic detail for applications from wall murals and event signage to retail displays. Achieve a high-quality look with this versatile, easy-to-handle, repositionable self-adhesive fabric—ideal for a wide range of indoor and outdoor applications.

Target customers	Applications	Benefits
Print service providers	Wall murals	Designed for easy installation, repositioning, and removal for a wide range of applications
Government agencies	Wall cut-outs	Ability to contour cut and apply without stretching
Graphic artists	Indoor and short-term outdoor signage	Smooth, matte finish for deep blacks, vivid colors, and high ink saturation
Sign shops	Point-of-purchase displays	Outstanding photographic image quality
Retail	Trade show graphics	B1, ASTM E84 flame resistance ⁴
	Decals	Compatible with Original HP Bright Office Inks, HP Vivid Photo Inks, HP PageWide XL pigment inks, and HP Latex Inks
	Window graphics	Slip resistant ⁵ for floor graphics ⁶
	Floor graphics	



Technical specifications

Ink compatibility	Compatible with HP Bright Office Inks, HP Vivid Photo Inks, HP PageWide XL pigment inks, and HP Latex Inks			
Weight (With liner)	289 g/m ² per ISO 536 Test Method			
Thickness (With liner)	304 microns/12 mil per ISO 20534 Test Method			
Liner	120 g/m ² , double-sided PE-coated silicone paper			
Adhesive	Clear, removable, and repositionable adhesive			
Removability	Up to 3 years removable/repositionable indoors			
Opacity	>85% per TAPPI T-425 Test Method and ISO 2471 Test Method			
Brightness	>97 per TAPPI T-452 Test Method			
Whiteness	118 per ASTM E313-98 Test Method			
Finish	Matte			
Slip rating	In compliance according to ANSI A137.1/A326.3 and AS HB198:2014 (AS/NZS 4586) ⁵			
Operating temperature	15 to 25° C / 59 to 77° F			
Operating humidity	20 to 80% RH			
Water resistance	Moderately water-resistant ⁷			
Wind orientation	Print side out			
Core size	3-in core with a removable 2-in core adapter			
Dry time	Immediate			
Flame resistance	B1, and ASTM E84 approved fire certifications ⁴			
Lamination	For additional protection, liquid or spray coatings are recommended ⁸			
HP PageWide XL cutter	The weight of this material is higher than the recommended weight limit for the HP PageWide XL cutter, which may reduce the expected life of the cutter			
Shelf life	1 year, unopened in original packaging			
Storage temperature	10 to 27° C / 50 to 80° F			
Storage humidity	35 to 65% RH			
Environmental	Adhesive fabric made with recycled water bottles ² and coating materials, REACH compliant ⁹			
Finishing/post processing	Use a carbide knife for kiss and die cutting			
Installation tip	To install the graphic, peel 101 millimeters (4 inches) of the release liner off the graphic and place on wall or surface. Continue to peel back 101 millimeters (4 inches) of the liner incrementally while mounting.			
Country of origin	Product of China			
Ordering information	Product numbers	Roll sizes	UPC	Region
	5L2S6A	610 mm x 30,5 m (24 in x 100 ft)	848412026474	United States, Canada, Latin America, Europe, Middle East, and Africa
	5L2S7A	914 mm x 30,5 m (36 in x 100 ft)	848412026481	United States, Canada, Latin America, Europe, Middle East, and Africa
	5L2S8A	1067 mm x 30,5 m (42 in x 100 ft)	848412026498	United States, Canada, Latin America, Europe, Middle East, and Africa
	5L2S9A	1372 mm x 30,5 m (54 in x 100 ft)	848412026504	United States, Canada, Latin America, Europe, Middle East, and Africa
	5L2T0A	1524 mm x 30,5 m (60 in x 100 ft)	848412026511	United States, Canada, Latin America, Europe, Middle East, and Africa
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/MediaWarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .			

- ¹ Product consists of PET fabric and coatings. With liner attached, 72% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.
- ² 100% of total PET resin in the product made from recycled water bottles. The coating does not contain recycled materials. Compliant with Global Recycled Standard (GRS) Version 4.0.
- ³ According to "The Ecology of Recycling," published on United Nations website, UN Chronicle, see un.org/en/chronicle/article/ecology-recycling and "Reducing and Reusing Basics," US EPA, March 2022, see <https://www.epa.gov/recycle/reducing-and-reusing-basics>.
- ⁴ B1, ASTM E84 approved fire certifications.
- ⁵ Slip resistance for dry environments based on testing by Sotter Engineering Corporation, February 2022, in compliance according to ANSI A137.1/A326.3 and AS HB198:2014 (AS/NZS 4586).
- ⁶ Recommended on indoor smooth, non-porous, sealed flat and dry surfaces for up to 3 months. Slip resistance for dry environments based on testing by Sotter Engineering Corporation, February 2022, in compliance according to ANSI A137.1/A326.3 and AS HB198:2014 (AS/NZS 4586).
- ⁷ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLFMedia.com/hp/printpermanence.
- ⁸ For additional protection, we recommend Marabu ClearShield Professional Wall Armor.
- ⁹ See the HP REACH Declaration published at HP.Printing.Products.and.Consumable.Supplies

For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2023 HP Development Company, L.P. © 2023 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group under license from HP Development Company, L.P.

