




HP Production Adhesive Vinyl, 3-in Core for HP PageWide Technology



The HP large format printing system—the complete solution

HP PageWide XL printers, Original HP PageWide XL pigment inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



¹ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 published at [HP Printing Products and Consumable Supplies](#). Logo source: Copyright European Chemicals Agency.

² Compatibility with HP DesignJet printers requires 3-in core adapter.

Quality prints for day-to-day production

Offer a range of indoor and outdoor displays

Produce vibrant color for your day-to-day production needs. Eye-catching displays—with a permanent, pressure-sensitive adhesive—are ideal for indoor and outdoor applications.

See application and finishing versatility

Designed for a variety of applications and finishing techniques, HP Production Adhesive Vinyl, 3-in Core is a highly versatile media compatible with a variety of laminates to meet a wide range of application needs.

Provide environmental reassurance

Meet the environmental goals of your company and your clients with this REACH compliant¹ vinyl.

| Target customers | Applications | Benefits |
|-------------------------|-------------------------------|---|
| Advertising agencies | Indoor and outdoor signage | Outstanding image quality for day-to-day production |
| Graphic artists | POP and retail displays | Fast dry time for easy handling |
| Sign shops | Trade show and event displays | Designed for a range of applications and finishing methods |
| Print service providers | | REACH compliant ¹ |
| | | Compatible with HP PageWide XL and HP DesignJet printers ² |

Technical specifications



HP Production Adhesive Vinyl, 3-in Core for HP PageWide Technology

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/paperpresets.

| | | | | |
|----------------------------------|---|-----------------------------------|------------------|---|
| Ink compatibility | Original HP PageWide XL pigment inks and Original HP DesignJet inks ³ | | | |
| Weight (without liner) | 160 g/m ² per ISO 536 Test Method | | | |
| Weight (with liner) | 300 g/m ² per ISO 536 Test Method | | | |
| Thickness (without liner) | 144 microns/5.7 mil per ISO 534 Test Method | | | |
| Thickness (with liner) | 271 microns/10.7 mil per ISO 534 Test Method | | | |
| Adhesive | Solvent, acrylic permanent adhesive | | | |
| Adhesion, initial | > 5 N/in after 20 minutes over stainless steel | | | |
| Adhesion, 24-hour dwell | > 10 N/in after 24 hours over stainless steel | | | |
| Dimensional stability (%) | Less than 5% over aluminum | | | |
| Elongation at break | >100% MD; >100% CD | | | |
| Opacity | Greater than 99% per TAPPI T-425 Test Method and ISO 2471 Test Method | | | |
| Brightness | 100% per ISO 2470 Test Method | | | |
| Whiteness | 127 per ISO 11475 Test Method | | | |
| Finish | Matte | | | |
| Operating temperature | 15 to 30° C / 59 to 86° F | | | |
| Operating humidity | 20 to 65% RH | | | |
| Dry time | Instant dry | | | |
| Lamination | Cold lamination, can be laminated with most commercially available cold laminate films | | | |
| Shelf life | 1 year, unopened in original packaging | | | |
| Storage temperature | 15 to 30° C / 59 to 86° F | | | |
| Storage humidity | 20 to 65% RH | | | |
| Printer setting | Recommend using HP Matte Polypropylene as the media setting for HP PageWide XL printers | | | |
| Country of origin | Product of China | | | |
| Ordering information | Product numbers | Roll sizes | UPC codes | Region |
| | 1AF11A | 914 mm x 45,7 m (36 in x 150 ft) | 848412020748 | United States and Canada |
| | 2HY31A | 1016 mm x 45,7 m (40 in x 150 ft) | 848412021905 | United States, Canada, Latin America, Europe, Middle East, and Africa |
| Warranty | HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/mediawarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus . | | | |

³ Compatibility with HP DesignJet printers requires 3-in core adapter.



For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2022 HP Development Company, L.P. © 2022 Brand Management Group. The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group on license from HP Development Company, L.P.

